




Sigen Energy Controller

5.0 – 25.0 kW Three Phase

- EMS inside for precise control
- DC ground-fault protection
- Multi-source black start
- On & off-grid compatibility
- DC/AC ratio up to 1.6
- IP66 system protection rating

Sigen Energy Controller 5.0–25.0 kW Three Phase

SigenStor EC	5.0 TP	6.0 TP	8.0 TP	10.0 TP	12.0 TP	15.0 TP	17.0 TP	20.0 TP	25.0 TP	Units
DC Input (from PV)										
Max. PV power	8000	9600	12800	16000	19200	24000	27200	32000	40000	W
Max. DC input voltage	1100									V
Nominal DC input voltage	600									V
Start-up voltage	180									V
MPPT voltage range	160 ~ 1000									V
Number of MPP. trackers	2			3			4			
Number of PV strings per MPPT	1									
Max. input current per MPPT	16									A
Max. short-circuit current per MPPT	20									A
AC Output (on-grid)										
Nominal output power	5000	6000	8000	10000	12000	15000	17000	20000	25000	W
Max. output apparent power	5500	6600	8800	11000	13200	16500	18700	22000	27500	VA
Nominal output current	7.6	9.1	12.2	15.2	18.2	22.8	25.8	30.4	38.0	A
Max. output current	8.4	10.0	13.4	16.7	20.1	25.1	28.4	33.4	41.8	A
Nominal output voltage	380 / 400									V
Nominal grid frequency	50 / 60									Hz
Power factor	0.8 leading ~ 0.8 lagging									
Total current harmonic distortion	THDi < 2%									
Efficiency										
Max. efficiency	98.1%	98.2%	98.3%	98.3%	98.3%	98.3%	98.3%	98.3%	98.3%	
European efficiency	96.1%	96.6%	97.1%	97.5%	97.7%	97.9%	97.9%	97.9%	98.0%	
AC Output (backup)										
Peak output power (10 seconds)	7500	9000	12000	15000	18000	22500	25500	30000	30000	W
Nominal output voltage	380 / 400									V
Nominal output frequency	50 / 60									Hz
Power factor	0.8 leading ~ 0.8 lagging									
Total voltage harmonic distortion	THDv < 2%									
Disruption time of backup switch ¹	0									ms
Battery Connection										
Battery module models	SigenStor BAT 5.0 / 8.0									
Number of modules per controller	1 ~ 6									pcs
Battery module voltage range	600 ~ 900									V
Protection										
Safety protection feature	DC ground fault protection, Arc fault circuit interrupter, DC reverse polarity protection, Insulation monitoring, Residual current monitoring, Type II DC/AC surge protection, Anti-islanding protection, AC overcurrent/overvoltage/short-circuit protection.									
General Data										
Dimensions (W / H / D)	700 / 300 / 260									mm
Weight	36									kg
Storage temperature range	-40 ~ 70									°C
Operating temperature range	-30 ~ 60									°C
Relative humidity range	0% ~ 95%									
Max. operating altitude	4000									m
Cooling	Smart air cooling									
System ingress protection rating	IP66									
Communication	WLAN / Fast Ethernet / RS485 / Sigen CommMod (4G/3G/2G)									
Standard Compliance										
Standard ²	IEC/EN 62109-1, IEC/EN 62109-2, IEC/EN 61000-6-1, IEC/EN 61000-6-2									

- ¹ This refers to the load-side disruption time, to achieve this functionality Sigen Energy Gateway needs to be used together with Sigen Energy Controller and Sigen Battery. Test conditions: In the open-circuit state of the power grid, the nominal power of the Sigen Energy Controller is higher than the total power of the home loads.
- ² For all standards refer to the certificates category in the Sigenenergy website.

Disclaimer: The information in this file is provided on an "as is" basis. To the fullest extent permitted by law, Sigenenergy Technology Co., Ltd. excludes all representations and warranties relating to this file and its contents or which is or may be provided by any affiliates or any other third party, including in relation to any inaccuracies or omissions in this file.